## Symbx<sup>®</sup>

## S-15 GENERAL PURPOSE TORCH

The S-15 torch is designed for general purpose gouging applications. The S-15 torch is used by:

- Fabricators, tank shops, shipyards, heavy industrial plants, construction firms, quarries and mines.
- For plate edge preparation, back/gouging welds, removal of old or defective welds.
- Ideal for repair and general maintenance of equipment.

The torch will accommodate round electrodes ranging in size from 5/32" (3.97mm) through 1/2" (12.7mm) and flat electrode sizes 3/8" x 5/32" x 12" and 5/8" x 3/16" x 12".

The S-15 torch is rated up to 1000 amperes. The following is the Part # for each torch assembly and part breakdown:

## **S-15 TORCH OPTIONS**


DESCRIPTION	TORCH LESS CABLE	TORCH W/ CABLE	CABLE
S-15 Torch w/3-Hole Head	30003	40003	
S-15 Torch w/Terminator Head	30005	40005	
S-15 Torch w/Terminator Head, 7' 360° Cable, Long Boot		40007	
S-15 Torch w/Terminator Head, 10' 360° Cable, Standard Boot		40008	
S-15 Torch w/Terminator Head, 10' 360° Cable, Long Boot		40009	
S-15 7' Cable w/Standard Boot			20658
S-15 10' Cable w/Standard Boot	t		20635
S-15 7' Cable w/Long Boot			20628
S-15 10' Cable w/Long Boot			20637

C.H. Symington & Co., Inc.

Main Office: 6063 Frantz Road, Ste.103, Dublin, Ohio 43017 Phone: (614) 766-2602 Web site: www.chsymington.com

**FAX:** (614) 766-2715 **E-Mail:** symex@aol.com

Warehouse/Shop: 10 Point Street, Carroll, Ohio 43112



REF	# DESCRIPTION	PART#
1	Handle	10030
2	Body	10031
3	Lever Assembly	10032
4	Upper Arm	10033
5	Valve Bonnet Assembly (incl.ref.# 6-8-9)	
6	Spanner Wrench	
7	Black O-Ring (2 required)	
8	Valve Spool Assembly includes:	
	Button (long)	10063
	O-Ring (2 required)	
	Valve Spool (brass center)	
	Button (short)	
9	Bonnet	
10	Hinge Pin	10066
11	Terminator Head Assembly	
12	Spring	
13	Insulator Assembly	
14	Insulator Screw only	
15	Head Screw only	
16	Lever Screw only	10092
NS	Wave Lock Washer for Head Assembly	